



Product Data Sheet

Water Tight Technologies, LLC
P.O. Box 899
Payson, AZ 85547
www.britenez.com

Water Cut-Off Mastic

Description:

Water Cut-Off Mastic is a tacky rubber-like compound used as a sealant or water stop for both *RUBBERALL*® and *BRITE-n-EZ*™ products and carries the *RUBBERALL*® brand on the packaging. This mastic is typically used as a waterproof barrier, in the form of a compression gasket, for the mechanically attached areas of the roof detail such as under termination bar and pipe boot clamps. It can also be used as a temporary overnight sealant or water stop.

It is typically applied with a caulking gun. This mastic cures by solvent evaporation to a tacky rubber, exhibiting excellent water resistance.

Physical Properties:

PROPERTY	PHYSICAL PROPERTIES
Color	Gray paste
Hazardous (Solvent) Components	Heptane (CAS# 142-82-5)
Specific Gravity	1.33
Solids Content	86%
VOC	1.47 lbs / gal.
Flash Point	14° F
Weight	10.9 lb per gallon

Application Instructions:

Surface to which *Water Cut-Off* is applied must be clean, dry and free from loose and foreign materials, oils and grease. Apply *Water Cut-Off* as follows:

1. Clean surfaces to be attached prior to applying *Water Cut-Off*.
2. Using a caulk gun, apply a bead of *Water Cut-Off* that is 1/2" thick by 1/2" wide, centering the bead directly over the cleaned area to be mechanically attached.
3. Attach the termination bar or pipe boot without smearing the *Water Cut-Off* outside of the attachment area.

Product Data:

Available Sizes: 10.1 oz tubes

Carton Size: 25 tubes per carton

Coverage: 1/2" wide bead is 10 linear feet per tube.

Storage: Store in original unopened containers, at temperatures between 60° and 80° F. When exposed to lower temperatures, restore to room temperature prior to use.

Shelf Life: The shelf life is approximately 12 months if stored in original unopened containers at temperatures between 60° and 80°F. Shelf life will be shortened if exposed to sustained elevated temperatures. **ROTATE STOCK.**

Precautionary Data:

This product is flammable. Keep away from fire, sparks, and sources of heat. Do not smoke. Close container after use. Avoid prolonged contact with skin as product may cause possible skin irritations and/or allergic sensitivity.

Use only in well ventilated areas.

For professional/industrial use only.

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects, or other reproductive harm.